
The Timken Company
4500 Mt Pleasant St. NW
N. Canton, OH 44720
Phone: (234) 262-3000
E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Part Number SUCAT205-16-IP69K/FVSL613, Corrosion-Resistant Take-Up Mounted Bearings - Set Screw Locking





Specifications | Dimensions | Basic Load Ratings

Specifications

Bore Size	1.0000 in
Seal Type	IP69K Seal
Housing Material	Machined Stainless Steel
Bearing Number	SUC205-16-IP69K/FVSL613
Lubrication Type	Food Grade Solid Lube
Locking Style	Set Screw Locking
Housing Construction	Take-Up
Bearing Style	Ball Bearing


Dimensions

Total Length L	3.813 in 96.8 mm
Total Height H	3.620 in 92.2 mm
Adjustment Screw Bore N	0.656 in 16.7 mm
Openinig Width N1	0.620 in 15.7 mm
Openinig Width N2	1.438 in 36.6 mm
Slot Width A1	0.540 in 13.7 mm
Pitch Height H1	3.000 in 76.2 mm
Height H2	2.250 in 57.2 mm
Shaft Length L1	2.438 in 61.9 mm
Dimension L2	0.380 in 9.7 mm
Center of Bearing from Bearing End S	0.563 in 14.3 mm
Inner Ring Width B	1.343 in 34.1 mm

Basic Load Ratings

Dynamic Load Rating[1]	2676 lbf 11900 N
Static Load Rating	1417 lbf 6300 N

[1] Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values.



Bearing Number	SUC205-16-IP69K/FVSL613				
Load Ratings - C_r	2676	lbf	11900	N	
Load Ratings - C_{0r}	1417	lbf	6300	N	
Lubrication Type	Food Grade Solid Lube				
Housing Material	Machined Stainless Steel				

TIMKEN

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

SUCAT205-16-IP69K/FVSL613

Corrosion-Resistant Take-Up Mounted Bearings - Set Screw Locking

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY